

SPRAYMATE MINI POT ACRYLIC

1. PRODUCT IDENTIFICATION AND COMPANY DETAILS

Product Name: **Mini Pot Acrylic**
Company Name: Spraymate cc
Address: 71 kroonarend Street
Randvaal
Gauteng
Telephone: (016) 365 5150
Fax: (016) 365 5159
Emergency: 083 776 3308

1. DESCRIPTION

Acrylic type water-based paint, which dries to a sheen finish.

2. USES

- Good quality washable wall finish for interior and exterior use.

3. ADVANTAGES

- Provides good wash ability.
- Dries to a smooth sheen finish.
- Easy application with a roller or a brush.
- Quick drying with good re-coating properties.
- Provides good opacity and exterior durability.

4. TECHNICAL DATA

- Colour White, black and a range of colours.
- Drying Time:

Surface Dry	30 minutes - 1 hour
Hard dry	3-4 hours
Recoatable	4 hours
- Solids (mass) $\pm 42\%$
- Finish Sheen
- Practical Spreading rate $6\text{m}^2/$ depending on surface porosity.
- Shelf Life 6 months from date of shipment in unopened original containers stored at temperatures below 30°C .
- Storage Store under cover at temperatures below 30°C

5. SURFACE PREPARATION

- The performance of this coating will depend on the degree of surface preparation.
- Surfaces must be clean dry and free from all grease and other contaminants.
- Apply to correctly prepared and primed substrates. Consult our Technical Division for correct choice of primer.

- Material is supplied as a single pack. Mix thoroughly until homogeneous and occasionally during use.
- Conventional Suitable Nozzle size: 1.4 – 1.8mm
Spray: Pressure at tip: 2.5-3.0 bar
Thin up to 15%
- Brush or Roller Suitable
- If applied by brush several coats will be required to obtain the desired film thickness.
- Drying times will depend on the applied film thickness and prevailing ambient conditions.
- Surface temperature must always be 3°C above dewpoint.
- Thinner: Water
- Cleaner: Water
- Clean all equipment immediately after use. Empty containers and surplus paint should be disposed of in accordance with approved regional regulations.

- Do not apply to metal surfaces directly.
- Do not apply during wet or cold weather below 5°C.

- Product contains flammable materials, keep away from sparks and open flames.
- Refer to the MATERIAL SAFETY DATA SHEET (MSDS).

The information contained herein is to the best of our knowledge correct and accurate and is meant to guide the specifier or user. Any recommendations or suggestions, which may be made, are without guarantee, since we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product.

VALIDITY DATE:

ISSUE DATE: 01-08-2005