1



# KRUD KUTTER® MOLD & MILDEW STAIN REMOVER

# **DESCRIPTION AND USES**

Krud Kutter<sup>®</sup> Mold & Mildew Stain is a professional strength formula that removes tough stains from mold and mildew and protects as it cleans. It is safe, fast and effective on most interior and exterior surfaces.

It works on tile, grout, tubs, fiberglass, shower doors, vinyl curtains, counters, sinks, and no wax floors. Also ideal for wood, vinyl, and aluminum siding, patio furniture, boats and more.

Not recommended on varnished surfaces.

#### **PRODUCTS**

SKU	Description	
MS324	32 oz. Trigger Sprayer	
MS012	1-Gallon	
MS323	32 oz. Trigger Sprayer	
MS05	5-Gallon	

## PRODUCT APPLICATION

#### **DIRECTIONS**

Always test on inconspicuous area first. For initial application, spray sparingly on surface to be cleaned, working from top to bottom. Spray surface until thoroughly wet, and allow to penetrate for 5 minutes before rinsing or wiping with wet cloth or sponge. To remove tough mold and mildew stains use a brush. Severe stains may need two cleanings. This product may not be able to remove mold and mildew stains imbedded in hard water deposits, old grout or silicone caulking. To prevent mold and mildew stains, a spray mist application every 1 to 2 months without scrubbing or rinsing will build up an invisible shield to protect the surface.

**CAUTION: EYE AND SKIN IRRITANT.** In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention.

KEEP OUT OF REACH OF CHILDREN.

Form: GDH-542 Rev.: 033018



## **TECHNICAL DATA**

# KRUD KUTTER® MOLD & MILDEW STAIN REMOVER

# PHYSICAL PROPERTIES

		MOLD & MILDEW STAIN REMOVER	
Composition		Proprietary Ingredients in a Water-based Solution	
Solvents		Water	
Weight	Per Gallon	8.33 lbs.	
	Per Liter	1.0 kg	
Color		Light yellow	
Clarity		Clear	
Odor		Mild	
pH (Concentrate)		10-11	
VOC (Weight %)		0.5%	
Practical Coverage		Varies with type and porosity of surface	
Shelf Life		NA	
Flash Point		>200°F (93°C)	
Caution!		CAUTION: EYE AND SKIN IRRITANT. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed take large amounts of water. Do not induce vomiting. Get medical attention.  KEEP OUT OF REACH OF CHILDREN.	
Safety Information		For additional information, see SDS	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, Illinois 60061

Phone: 877•385•8155 www.rustoleum.com Form: GDH-542 Rev.: 033018