


<b>THINNER</b>	<b>TECHNICAL DATA</b>	<b>ATO-06</b>
	<b>CALIPER CLEANER</b>	

## DESCRIPTION AND USES

Rust-Oleum® Caliper Cleaner removes contaminants from brake calipers and drums such as brake fluid, grease, and oil. Use prior to painting calipers with Rust-Oleum Caliper Paint.

## PRODUCTS

SKU	Description
251597	Caliper Cleaner

## PRODUCT APPLICATION

### PAINTING CONDITIONS

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50-90°F (10-32°C). Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

### SURFACE PREPARATION

Brake dust may contain asbestos. Remove all loose brake dust with an enclosed cylinder/HEPA vacuum. To reduce exposure to air-borne asbestos fibers, do not use Caliper Cleaner to remove dry or loose dirt.

## PRODUCT APPLICATION (cont.)

### APPLICATION

Shake can vigorously for one minute. Shake often during use. Hold can 10-16" from the surface and spray in a steady back-and-forth motion and allow to run off or wipe dry with a clean cloth. Repeat as necessary for areas with heavy deposits. Do not apply to brake linings, painted surfaces, plastic, or parts made of rubber. Do not use near open flame.

### CLEAN-UP

Properly discard empty container in trash container. Do not burn or place in home trash compactor.

### CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

## PHYSICAL PROPERTIES

Physical Properties	CLAIPER CLEANER
Composition	Blend of Acetone and Aromatic Hydrocarbons
MIR	0.60 Max
Fill Weight	11 ounces
Practical Coverage	4-8 calipers/can
Shelf Life	5 years
Flash Point	-156°F (-104°C)
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.