

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

Rippled Effect

Add a Textured Finish to Glass



Ideal for glass lamps, candle holders, vases and more

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR.
VAPORS MAY CAUSE FLASH FIRE.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 11 OZ. 312g

NO SOMETER A PRESIÓN.

OBSERVAR OTRAS PRECAUCIONES AL DORSO.

Rippled Effect Clear is an innovative coating that creates a rippled effect with a wet glass texture. Rippled Effect is a semi-transparent clear coating that transforms the texture of the glass, but still allows light to pass through. It is ideal for glass vases, candle holders, lamps, window panes and more. For indoor use only.

Painting Conditions: Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C) or galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

Preparation: Clean surface thoroughly with glass cleaner or soap and water, using a lint free cloth. Allow glass to dry completely before painting.

Painting: Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. For a finer texture, hold the can upright 12-14 inches from the surface, spray in a steady back and forth motion. Apply using very thin coats. For a larger texture, hold the can upright 10-12 inches from the surface and spray in a slow but steady back and forth motion. The wet look will appear shiny once applied to the surface. Apply 3-5 coats. The more coats applied, the more the effect will show.

Dry & Recoat Times based on 70%-50% relative humidity. Dries completely in 15-20 minutes. May recoat anytime.

Clean-up: Wipe off tip before storing. Clean up wet paint with Xylol or mineral spirits. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

Clogging: If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick pin or other object into the stem.

Please Note: Rippled surfaces may be cleaned with a soft cloth or hand washed with soap and water.

CONTAINS: ACETONE AND XYLENE. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. **Do not puncture, strike or incinerate (burn) container.** Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F. **NOTICE:** Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **Vapors may ignite explosively.** Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electrical motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Avoid contact with eyes, skin and clothing. **First Aid:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. **WARNING:** This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm. **KEEP OUT OF REACH OF CHILDREN.** Avoid repeated or prolonged contact with skin. Avoid contact with eyes. Wash thoroughly after handling. For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800) 481-4785. Conforms to ASTM D-4236.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact our Product Support Department at 1-800-481-4785 for a full refund of the purchase price. Refer to product number and batch code on bottom of can.

RUST-OLEUM
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

© 2013 Rust-Oleum Corporation Made in USA Hecho en E.U.A. 279028 1113



1-800-481-4785
rustoleum.com

Rippled Effect Clear es un revestimiento innovador que da la textura de cristal de vidrio mojado y añade elegancia a una pequeña pieza de vidrio. Rippled Effect es un recubrimiento semi-transparente, que transforma la textura del vidrio, pero todavía permite que la luz pase a través del mismo. Es ideal para floreros de vidrio, candelabros, lámparas, cristales de ventanas y más. Para uso solamente en artículos interiores.

For complete instructions in Spanish and additional application information, scan the QR code or visit rustoleum.com/rippled.

Para obtener instrucciones completas en ideas de aplicación Español y adicional, analizar el código QR o visite rustoleum.com/rippled.



ADVERTENCIA. CONTIENE: ACETONE Y XILENO. Vapores dañinos. Pueden afectar al cerebro o al sistema nervioso causando mareos, dolores de cabeza, o náusea. Causan irritaciones en los ojos, piel, nariz y la garganta. Haga contenedor no perforo, huelga o incinerar (quemar). Una exposición al calor o una prolongada exposición al Sol puede causar ruptura explosiva. No exponga al calor o almacene en temperaturas sobre 48°C (120°F). **AVISO:** Un mal uso intencional al deliberadamente concentrando y respirando el contenido puede ser dañino o fatal. Los vapores pueden encenderse explosivamente. Mantenga lejos del calor, chispas y las llamas. No fume. Apague las llamas y llamas pilotos, y apague las estufas, calentadores, motores eléctricos y todas las otras fuentes de ignición hasta que todos los vapores hayan desaparecido. Prevenga la acumulación de vapores abriendo todas las ventanas y puertas para lograr una ventilación cruzada. **Use solamente con una ventilación adecuada.** No respire el polvo, los vapores o la niebla del rociado. Asegure la entrada de aire fresco durante la aplicación y el secado. Si experimenta lagrimeo de los ojos, dolores de cabeza, o mareos, use protección para la respiración (aprobada por NIOSH) o salga del área. Evite contacto con los ojos, piel, y la ropa. **Primeros Auxilios:** Si es que sufre una dificultad al respirar, salga del área para obtener aire fresco. Si continua sufriendo una dificultad al respirar, obtenga inmediatamente asistencia médica. En caso de contacto con los ojos, enjuague inmediatamente con bastante agua por 15 minutos por lo menos y obtenga atención médica. Para contacto con la piel, lave completamente con jabón y agua. **ADVERTENCIA:** Este producto es conocido en el estado de California como causante de cáncer y defectos de nacimiento u otros daños reproductivos. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.** Evitar el contacto repetido o prolongado con la piel. Evite el contacto con los ojos. Lávese bien las manos después de utilizar el producto. En caso de emergencia, comuníquese con su médico, centro local para el control de venenos o clínica para emergencias. Para obtener más información sobre el producto y los posibles efectos en la salud, llame al (800) 481-4785. Conforma con ASTM D-4236. **PROHIBIDA SU VENTA A MENORES DE EDAD; PRODUCTO ORIGINARIO DE E.U.A.**

275999 RIPPLED EFFECT CLEAR



0 20066 23776 9