

**AUTOMOTIVE
TRIM & BUMPER PAINT SPONGE APPLICATOR****DESCRIPTION AND USES**

Rust-Oleum® Trim & Bumper Paint is designed to renew and restore the OEM finishes found on many vehicles. Trim & Bumper Paint is suitable for use on plastic and metal trim, moldings, rear view mirror covers, bumpers, and rub strips.

PRODUCTS

SKU (4 ounces)	Description
267719	Black

PAINTING APPLICATION**PAINTING CONDITIONS**

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50-80°F (10-26°C) and humidity is below 85% to ensure proper drying. For best results, do not paint in direct sunlight.

SURFACE PREPARATION

Remove all dirt, wax, and grease from the surface with Rust-Oleum® Wax & Tar Remover. Wash the area with a mild soap and water solution, fresh with fresh water, and dry with a clean cloth. Lightly sand uneven areas and remove all sanding dust.

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)**PRIMING**

To improve adhesion, a Rust-Oleum Primer is recommended when rust is present on the surface to be painted. Recommended primers include 249321 Primer Sealer or any of the sandable primers (249419 Red, 252472 Light Gray, or 249415 Gray).

APPLICATION

Use only with adequate ventilation. Without removing the cap, shake bottle for one minute. Recap and shake as needed during the painting process. Depress the sponge applicator tip in an inconspicuous area or on a piece of scrap material to start the paint flow. Apply paint using light pressure on the bottle. For best appearance, apply one coat of paint, let dry, and feather the edge. For even coverage, maintain a wet edge and with the sponge tip, smooth out any runs, drips, sags or excess paint. A foam brush may be used for hard to reach areas or to smooth out the paint finish. A second coat may be necessary for best coverage. Do not use near open flame.

DRY & RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20 minutes, to handle in 1 hour and fully dry in 24 hours. Allow 20 minutes dry time between coats.

CLEAN-UP

Wipe sponge applicator tip with a Rust-Oleum Paint Prep Wipe or with a rag dipped in mineral spirits to remove excess paint. Replace the cap tightly and store the bottle upright. Properly discard empty container.



TECHNICAL DATA

AUTOMOTIVE TRIM & BUMPER PAINT SPONGE APPLICATOR

PHYSICAL PROPERTIES

TRIM & BUMPER PAINT SPONGE APPLICATOR		
Resin Type		Modified Alkyd
Pigment Type		Carbon Black
Solvents		Aromatic Hydrocarbons
Fill Weight		4 ounces
VOC		339 g/l (2.82 lbs./gal.)
Recommended Dry Film Thickness (DFT) Per Coat		1.0-2.0 mils (25-50μ)
Practical Coverage at Recommended DFT		2-3 sq.ft./container
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	20 minutes
	Handle	1 hour
	Recoat	24 hours
Shelf Life		5 years
Flash Point		77°F (25°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.