



# AUTOMOTIVE PAINT FOR PLASTIC CLEAR

## DESCRIPTION AND USES

Rust-Oleum® Paint for Plastic Clear is recommended to be applied over Rust-Oleum Paint for Plastic colors to provide a high gloss, protective coating, or use directly on indoor and outdoor plastics to renew and revitalizes the surface. No primer is required. These sprays are suitable for use on automotive plastics, polypropylene, polystyrene, resin, PVC, and fiberglass, and vinyl plastics such as chairs, tables and planters. Note: Some plastics made of polyethylene such as Little Tikes® children's products are manufactured in a way that may hinder maximum paint adhesion. Test this product in an inconspicuous area to test for compatibility on the surface.

Rust-Oleum® Paint for Plastic Clear features an advanced spray system that allows you to spray at any angle, even upside down for those hard to reach areas. A comfort spray tip with a wider finger pad reduces fatigue caused by continuous spraying.

## PRODUCTS

254855 Clear (11 oz.)

## PAINTING APPLICATION

### PAINTING CONDITIONS

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50-90°F (10-32°C) and humidity is below 85% to ensure proper drying. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

### SURFACE PREPARATION

For new plastic surfaces, thoroughly wipe down surface with paint thinner to promote adhesion. For aged or weathered surfaces, remove loose material with a brush or scraper, clean with soap and water, rinse and let dry. If mildew is present, wash with a bleach solution, rinse and let dry.

## PRODUCT APPLICATION (cont.)

### APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 10-12" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart. Maximum adhesion is achieved in 5-7 days. Do not use near open flame.

### DRY & RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20-30 minutes, to handle in 1 hour and fully dry in 24 hours. Apply a second coat anytime.

### CLEAN-UP

Wipe off tip when finished. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

### CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

\* Little Tikes® is a registered trademark of Newell Rubbermaid.



## TECHNICAL DATA

# AUTOMOTIVE PAINT FOR PLASTIC CLEAR

### PHYSICAL PROPERTIES

		PAINT FOR PLASTIC
Resin Type		Acrylic
Pigment Type		NA
MIR		0.85 Max
Fill Weight		11 ounces
Solvents		Acetone, Butyl Acetate, Naphtha, Toluene
Recommended Dry Film Thickness (DFT) Per Coat		1.0-2.0 mils (25-50 $\mu$ )
Practical Coverage at Recommended DFT		8-15 sq. ft./can (0.90-1.4 m <sup>2</sup> /can)
Dry Times at 77°F (25°C) and 50% Rel. Hum.	Touch	20-30 minutes
	Handle	1 hour
	Recoat	Anytime
Shelf Life		5 years
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.