



SPECIAL FINISH SPRAY PAINT

PAINTING CONDITIONS

Use outdoors or in a well ventilated area. Use when temperature is between 10-32°C and humidity is below 65% to ensure proper drying. Avoid spraying in windy and dusty conditions. Cover surrounding area to protect from spray mist.

APPLICATION INFORMATION

Application conditions	Surface temperature between 10-32°C Relative humidity between 10% - 85%
Drying time	Surface dry 15- 30 minutes (Dry times will be extended during cold, wet or humid conditions)
Recoating time	Anytime
Clean up	Lacquer thinners
Substrates	Wood, metal, Wicker

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants with "A" grade lacquer thinners or methylated spirits. Soaps and detergents can also be used but a final clean with a suitable solvent is recommended. Be sure the substrate is completely dry, remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces.

APPLICATION METHOD

Shake can vigorously for 1 minute after mixing ball begins to rattle. If mixing ball fails to rattle DO NOT USE CAN. Contact Spraymate. Hold can upright 20 to 30cm from substrate and spray in steady back and forth motion, slightly overlapping each stroke. Keep the can in motion whilst spraying. Apply two or more light coats a few minutes apart to avoid drips and runs. **Do not use near open flame.**

Note: Inexperienced operators should practice on scrap surfaces to first get the "feel" for spray paint application.

CLEAN-UP

Clean valve immediately after use by turning can upside down and depressing the actuator for 3 to 5 seconds (some paint will be sprayed out, so be careful not to inadvertently spray yourself or other objects in the process)

CLOGGING

If the valve clogs, twist and pull off actuator and rinse in lacquer thinners. Do not insert any object into actuator orifice.



SPECIAL FINISH SPRAY PAINT

PHYSICAL PROPERTIES

Physical Properties	Spray paint	
Resin Type	Nitrocellulose lacquer	
Pigment type	Proprietary	
Solvents	Acetone, Methyl Ethyl Ketone, Toluene	
MIR	1.40 Max	
Fill	250ml	
Practical coverage	Approximately 0.9m ² - 1.0m ² per can	
Dry time at 21-27°C & 50% Relative humidity	Touch	20 Minutes
	Fully Dry	30 Minutes
	Recoat	Anytime
Dry heat Resistance	93°C	
Shelf life	5 years	
Flash point	0	
Safety information	For additional information see MSDS.	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Spraymate P Ltd
 71 Kroonarend road
 Randvaal
 1873

Tel: (016)365-5120
 Fax: (016)365-5159
 Web: spraymate.co.za
 Email: grant@spraymate.co.za