

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®**RIPPLED EFFECT****DESCRIPTION AND USES**

Rust-Oleum® Rippled Effect Clear is an innovative coating that creates a rippled effect with a wet glass texture. Rippled Effect is a semi-transparent clear coating that transforms the texture of the glass, but allows light to pass through. It is ideal for use on glass vases, candle holders, lamps and window panes. Rippled Effect features an advanced spray system that allows you to spray at any angle, even upside down for those hard to reach areas. A comfort spray tip with a wider finger pad to reduce fatigue caused by continuous spraying. For indoor use only.

PRODUCTS

SKU	Description
275999	Rippled Effect

PRODUCT APPLICATION**PAINTING CONDITIONS**

Use outdoors or in a well ventilated area such as an open garage. Use when the temperature is between 50-90°F (10-32°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces that will exceed 200°F (93°C) or on galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

Clean surface thoroughly with glass cleaner or soap and water using a lint-free cloth. Allow glass to dry completely before painting.

PRODUCT APPLICATION**APPLICATION**

Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. For a finer texture, hold the can upright 12-14 inches from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Apply using very thin coats. Keep the can the same distance from the surface and keep the can in motion while spraying. For a larger texture, hold the can upright 10-12 inches from the surface and spray in a slow but steady back and forth motion keeping the can the same distance from the surface and in motion while spraying. The wet look will appear shiny once applied to the surface. Apply 3-5 coats. The effect will be enhanced by more applied coats.

DRY & RECOAT TIMES

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Dries tack free in 5 minutes and will be completely dry in 15-20 minutes. It may be recoated at anytime. Note: Once dry, the rippled surface may be cleaned with a soft cloth or hand washed with soap and water.

CLEAN-UP

Wipe off tip before storing. Clean up wet paint with xylene or mineral spirits. Properly discard of empty container. Do not burn or place in home trash compactor.

CLOGGING

If valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not stick pin or other object into the stem.

TECHNICAL DATA

RIPPLED EFFECT

PHYSICAL PROPERTIES

		RIPPLED EFFECT
Resin Type		Acrylic Lacquer
Pigment Type		NA
Solvents		Acetone, Methyl Ethyl Ketone, N-Butyl Acetate, Xylene
MIR		1.40 Max
Fill Weight		11 ounces
Recommended Dry Film Thickness (DFT) Per Coat		1.0-2.5 mils (25-62.5μ)
Wet Film to Achieve DFT		8.0-18 mils (200-450μ)
Practical Coverage at Recommended DFT		10-11 sq.ft./can (0.9-1.02 m ² /can)
Dry Times at 70°F (21°C) and 50% Relative Humidity	Tack Free	5 minutes
	Handle	10 minutes
	Recoat	Anytime
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.