

SAFETY DATA SHEET

SPRAYMATE MINI POT ACRYLIC BRUSH ON

According to Regulation (EC) No 1907/2006

1. PRODUCT IDENTIFICATION AND COMPANY DETAIL

Product Name: **Mini Pot Enamel**
Company Name: Spraymate cc
Address: 71 kroonarend Street
Randvaal
Gauteng
Telephone: (016) 365 5150
Fax: (016) 365 5159
Emergency: 083 776 3308

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

ENVIRONMENT

The product contains a substance which is toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

PHYSICAL AND CHEMICAL HAZARDS

The product is highly flammable, and explosive vapours/air mixtures may be formed even at normal room temperatures.

HUMAN HEALTH

Irritating and degreasing to skin.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
DISTILLATES (PETROLEUM), LIGHT DISTILLATE, HYDROTREATED	270-093-2	68410-97-9	10-30%	Xn;R65. Xi;R38. F;R11. N;R51/53. R66.
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	265-151-9	64742-49-0	10-30%	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.
MINERAL SPIRITS	232-489-3	8052-41-3	10-30%	Xn;R65. N;R51/53. R10,R66.
ETHYL 3-ETHOXY PROPIONATE	212-112-9	763-69-9	5-10%	Xi;R36.
XYLENE	215-535-7	1330-20-7	5-10%	R10 Xn;R20/21 Xi;R38
ETHYLBENZENE	202-849-4	100-41-4	1-5%	F;R11 Xn;R20
2-METHOXY-1-METHYLETHYL ACETATE	203-603-9	108-65-6	< 1%	R10 Xi;R36
SOLVENT NAPHTHA, LIGHT AROMATIC	265-199-0	64742-95-6	< 1%	Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.
AMORPHOUS SILICA		112926-00-8	0-7 %	Xi;R37.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

Rinse mouth thoroughly. Do not induce vomiting. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash the skin immediately with soap and water.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Water spray, fog or mist. Foam, carbon dioxide or dry powder.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

DO NOT touch spilled material. Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Read and follow manufacturer's recommendations.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Keep containers tightly closed. Store above freezing.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
2-METHOXY-1-METHYLETHYL ACETATE	WEL	50 ppm	274 mg/m3	100 ppm	548 mg/m3	Sk
AMORPHOUS SILICA	WEL		2,4 mg/m3			
ETHYLBENZENE	WEL	100 ppm	441 mg/m3	125 ppm	552 mg/m3	Sk
XYLENE	WEL	50 ppm	220 mg/m3	100 ppm	441 mg/m3	Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

ENGINEERING MEASURES

Provide adequate ventilation.

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves.

HYGIENE MEASURES

Wash promptly if skin becomes contaminated.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Viscous Coloured liquid

COLOUR Misc. colours

ODOUR Aromatic hydrocarbons

SOLUBILITY	Immiscible with water Soluble in Organic solvents.		
BOILING POINT (°C)	82-205 °C 760 mm Hg	FLASH POINT (°C)	~12 °C CC (Closed cup).

10 STABILITY AND REACTIVITY

STABILITY

No particular stability concerns.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

11 TOXICOLOGICAL INFORMATION

INHALATION

Vapours may cause drowsiness and dizziness.

SKIN CONTACT

Irritating to skin. Product has a defatting effect on skin.

HEALTH WARNINGS

This chemical may cause skin/eye irritation. Vapour from this chemical can be hazardous when inhaled.

MEDICAL SYMPTOMS

Skin irritation. Irritation of eyes and mucous membranes. Upper respiratory irritation. Drowsiness, dizziness, disorientation, vertigo.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

No specific disposal method required. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS	3		
PROPER SHIPPING NAME	PAINT RELATED MATERIAL		
UN NO. ROAD	1263	UK ROAD PACK GR.	II
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	II	TUNNEL RESTRICTION	(D/E)
HAZARD No. (ADR)	33	ADR LABEL NO.	3
HAZCHEM CODE	3YE	RID CLASS NO.	3
RID PACK GROUP	II	UN NO. SEA	1263
IMDG CLASS	3	IMDG PACK GR.	II
EMS	F-E, S-E	UN NO. AIR	1263

15 REGULATORY INFORMATION

LABELLING



Irritant



Highly Flammable

SAFETY PHRASES

S2	Keep out of the reach of children
S24/25	Avoid contact with skin and eyes.

POISONS SCHEDULE (Aust): S5

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16 OTHER INFORMATION

REVISION DATE 29-06-2009

RISK PHRASES IN FULL

R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R20/21	Harmful by inhalation and in contact with skin.
R36	Irritating to eyes.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER: All information and recommendations contained herein are given in good faith, but without guarantee in respect of accuracy. Spraymate accepts no responsibility for errors or omissions, nor the consequences thereof.